

Ultra compact portable systems

K289i/K289-Pro

- Compact, high output full-range system
- Wide coverage angles
- Coda Audio 1" patented compression driver
- Multiple fly-points for easy hanging



The K289 contains a pair of low frequency 8" cone drivers with 2" voice coils, and a 1" high frequency driver mounted on a 90° conical waveguide. All Pro enclosures include 14 x M6 mounting suspension points and an air cargo flying track. Applications include front of house, clubs, touring PA-systems and corporate events.

System components:


AC24

C-Series Amplifiers

PW115

PW118

PW18A



CU82V
U-bracket
vertical



68620
Truss clamp
vertical

AC24

Analog Signal Processor - see page 47 for further information.



TECHNICAL SPECIFICATIONS:

Type:	2-way full range
Application:	High quality short throw
Frequency response:	55 Hz - 30 kHz (-3 dB)
Power handling AES:	440 W
Program power:	880 W
Peak power:	1760 W
Sensitivity:	97.5 dB
Max. SPL peak:	130 dB
Dispersion:	90° Conical
Components:	
Low frequency:	2 x 8" / 2" voice coil ultra low distortion woofer
High frequency:	1" / 1.5" voice coil compression driver
Crossover point:	1900 Hz
Nominal impedance:	16 Ohm (K289-Pro), 4 Ohm (K289)
Input connectors:	2 x Neutrick™ NL4MP
Enclosure material:	15 mm plywood
Finish:	Textured black Paint
Flying Hardware:	3 x M6 (K289) 1 x AirCargo + 14 x M6 (K289-Pro)
Dimensions:	250 x 700 x 300 mm
Net weight:	17 kg (K289), 18 kg (K289-Pro)